

SLOTTED BARREL (M14 FIT) TILE DRILL BITS (TDXCEL)

TDXCEL SLOTTED BARREL TILE DRILL BITS

The Mexco Drill Bit Range offers maximum performance and cost per cut when drilling the hardest of man-made and natural decorative materials.

KEY FEATURES

- Slotted barrels for ease of stock removal and cooling
- Diamond tipped for a professional finish
- M14 thread for use with Angle Grinder
- No water required









Slotted barrel

Diamond tipped

No water required

USEFUL INFORMATION:

- Ensure you are using the correct type of machine for the drilling application (refer to the recommended RPM and machine instructions). Ensure all forms of percussion or hammer action are turned OFF.
- To start drilling, use a Mexco suction cup guide to enable an accurately positioned hole.
 Alternatively place the drill at a 30 degree angle. Drill until tile drill bit starts to penetrate the material. Once the hole has started to form, bring the drill up into the upright position and continue
- Periodically remove the bit from the cut to allow cooling.
- For horizontal drilling minimal pressure is required.
- For vertical drilling the weight of the machine will give sufficient pressure.
- · The tip of the drill bit will become HOT, please handle with care and wear suitable PPE.
- \cdot Use on high speed drill (1800rpm) predominately this will be a corded machine not a cordless.
- Only use for drilling the tile, not the material behind the tile. Use appropriate drill bit following penetration of tile.

PRODUCT OVERVIEW:

Grade: XCEL
Tip Type: Diamond
Dry/Wet: Dry

Recommended for: High-speed Drills, Angle Grinders



OPTIMUM COST PER CUT

The XCEL range of products are simply our best in class, due to an uncompromised use of raw materials in their manufacture they offer the user a cutting or drilling experience that is faster and cleaner with an optimum cost per cut.



PRODUCT DATA SHEET

DIAMETERS AVAILABLE:

| Code | Diameter (mm) |
|-----------|---------------|
| TDXCEL18 | 18 |
| TDXCEL20 | 20 |
| TDXCEL25 | 25 |
| TDXCEL32 | 32 |
| TDXCEL35 | 35 |
| TDXCEL38 | 38 |
| TDXCEL45 | 45 |
| TDXCEL50 | 50 |
| TDXCEL60 | 60 |
| TDXCEL68 | 68 |
| TDXCEL75 | 75 |
| TDXCEL82 | 82 |
| TDXCEL91 | 91 |
| TDXCEL110 | 110 |
| | |

RECOMMENDED FOR USE ON:

HIGH SPEED DRILL*



*Requires TDXM14HEX chuck adaptor

APPLICATION:

- Bathroom Fittings
- Kitchen Fittings
- Porcelain
- Ceramic Tiles
- Stone Tiles
- Stone Worktops











- RECOMMENDED to cut these materials
 - Will cut these materials with the possibility of reduced lifetime / glazing

PRODUCT DATA SHEET